



30 Amp Digital Solar Controller

➔ INCREASES BATTERY LIFE BY PREVENTING OVERCHARGING



Provides Superior Battery Protection

A Solar Controller is an essential component of your photovoltaic (PV) system. The Controller maintains the life of the battery by protecting it from overcharging. When your battery has reached a 100% state of charge, the Controller prevents overcharging by limiting the current flowing into the batteries from your solar array.

The GP-PWM-30 is a 12 volt flush mounted photovoltaic (PV) charge controller rated for a continuous solar current input of 30 amps and is capable of dual bank charging.

- Regulates current flow from your solar modules to your batteries
- Temperature compensated pulse width modulation (PWM) charging
- 3 Battery charging profiles: Sealed/Gel, AGM and Flooded
- 4 stage charging: Bulk, Absorption, Float and Equalize
- Maximum Power Boost Technology™ for manual bulk charge at any stage of the charge cycle
- Dual-bank battery charging
- On-off control for the following Go Power! Inverters: GP-SW1000, GP-HS-1500, GP-SW2000, GP-SW3000
- Back lit LCD screen displays charging current, battery voltage and battery state of charge
- Built-in USB charge port
- Heavy-duty terminals for low resistance connections
- Suitable for 12V solar systems up to 488 watts
- 5 year warranty

SPECIFICATIONS

Nominal System Voltage	12V
Max Solar Array Current	30A
Battery Voltage Range	6V -- 15.5V
Max. Solar panel input voltage	28V
Operating Consumption	6mA
Display Consumption	10mA
Temp. Compensation	-13mV/°F / - 24mV/°C
Operating Temperature	- 40 to 185°F / - 40 to 85°C
Humidity	99% N.C.
Dimensions (H x W x D):	4.25 x 7.48 x 1.38 in; 108 x 190 x 35 mm
Weight	10.6 oz; 300 g;
Maximum Wire Gauge:	#4 AWG
Warranty	5 years
Protection	Battery Reverse Polarity, Solar Array Reverse Polarity, Over temperature, Over Current

Charge voltages shown are at 77°F / 25°C. The total rated Maximum Power Current (Imp) of the PV input should not exceed 30 amps.

BATTERY CHARGING PROFILE	SEALED/GEL	AGM	FLOODED
Bulk Charge Voltage Set Point	14.1V	14.4V	14.4V
Absorption Charge Voltage (30 min / day)	14.1V	14.4V	14.4V
Max. Power Boost Charge Voltage: Automatic (2h if V < 12.3V)	14.1V	14.4V	14.4V
Max. Power Boost Charge Voltage: Manual (2h if activated)	14.1V	14.4V	14.4V
Float Charge Voltage	13.7V	13.7V	13.7V
Equalize Charge Voltage (2h / 28 days or after V < 12.1V)	Disabled	Disabled	14.9V

AUTHORIZED DEALER:

Specifications may be subject to change. Product may not be exactly as shown. Specifications subject to local environmental conditions. "Carmanah" and Carmanah logo are trademarks of Carmanah Technologies Corp. Carmanah is a Canadian public corporation - TSX-CMH.